



1966535B1 & US 7816843

Red OBSTAFLASH medium intensity flashhead including 6 red led projectors and a junction box to be used with the external obsta power cabinet. The complete product P/N113724 (flashhead P/N113736 + power supply P/N113727) is compliant with ICAO medium intensity

Flashhead

- ▶ 6 led projectors coming with molded cable
- ▶ 1 junction box
- Support for the 6 projectors and the junction box

This flashhead must be powered through obsta power cabinet.

- ▶ 110-240Vac power cabinet P/N113727 (for 1 up to 6 flashheads)
- Patents: EP + 48Vdc power cabinet P/N113755 (for 1 up to 6 flashheads)

Les dimensions sont en mm All dimensions are in mm Ø 500	I CONTRACTOR OF THE SECOND SEC
238 6x Ø 17.5 88 90° Ø 336.55	

Mechanical Characteristics		
Operating temperature	-40/+55°C	
Weight	5 kg	
Size of the light	315mm (height) x 500mm (diameter)	
Photometric Characteristics		
Effective light output night mode at 0° on site	2000cd (red) with IR	
Color night time	Red	
Horizontal beam spread	360°	
Standards		
Standards compliance	ICAO annex 14 chapter 6, FAA (AC 150/5345-43H), EASA, DGAC, CAA (CAP 168)	