




- Completely molded and perfectly waterproof
- Bird spike
- No grounding issue, class II
- Total 192 leds wired in 48 independant circuits of 4 leds each
- Luminous intensity 3 times higher than ICAO/FAA requirements

For installation on NPT 3/4", the NAVILITE must be fixed on its bracket below

  <small>MONTAGE 1 Mounting 1</small> <small>MONTAGE 2 Mounting 2</small> <small>ECHELLE 1/3 1/3 scale</small>		<b>Electrical Characteristics</b>	
		Wattage	12 W
		Current drawn	250 mA
		Life time	~10years
		Main voltage	48VDC ± 10%
<b>Mechanical Characteristics</b>			
		IP degree	IP66
		Wiring	On stripped wires
		Operating temperature	-40/+55°C
		Weight	950 g
		Size of the light	194mm (height) x 63mm (over diameter)
		Attachment	1 screw M5 provided
<b>Photometric Characteristics</b>			
		Luminous intensity	> 90 Cd
		Color night time	Red fixed
		Vertical beam spread	>10°
		Horizontal beam spread	360°
<b>Standards</b>			
		Standards compliance	ICAO annex 14 chapter 6, FAA AC 150/5345-43G
		Certification	FAA (AC 150/5345-43G) ETL verified

