

## Garniture pour la protection de câble conducteur ou de garde avec fibre optique



Garniture de sphère pour câble de garde et câble optique




Table 1: Armor Rods

| P/N*       | Min. (mm) | Max. (mm) | Length (mm) | Nbr of Rod | Rod Dia. (mm) | Weight (Kg) |
|------------|-----------|-----------|-------------|------------|---------------|-------------|
| 113750X085 | 8.54      | 10.01     | 1000        | 10         | 3.07          | 0.214       |
| 113750X100 | 10.02     | 11.51     | 1000        | 11         | 3.07          | 0.240       |
| 113750X115 | 11.52     | 13.26     | 1000        | 13         | 3.07          | 0.280       |
| 113750X132 | 13.27     | 15.50     | 1000        | 13         | 3.45          | 0.354       |
| 113750X155 | 15.51     | 17.80     | 1000        | 15         | 3.45          | 0.409       |
| 113750X178 | 17.81     | 18.50     | 1000        | 16         | 3.45          | 0.437       |
| 113750X185 | 18.51     | 21.28     | 1000        | 14         | 4.24          | 0.580       |
| 113750X212 | 21.29     | 23.00     | 1000        | 15         | 4.62          | 0.731       |
| 113750X230 | 23.01     | 24.40     | 1000        | 15         | 4.62          | 0.997       |

\*Final designation and part number to be confirmed at order time.  
\*Replace X by R or L, depending on cable lay direction. Contact us for different length.

### Caractéristiques Mécaniques

Diamètre de câble Ø8.54-24.40mm