

## ARMOR-RODS-Ø8.54-24.40 [P/N: 113750]

Armor Rods are recommended for the protection of conductors They protect conductors against bending, compression, abrasion etc. Armor Rods fit tightly the cable shape and prevent damage issue on conductors



- Easily hand applied
- Light weight
- ▶ Good grip on the conductor, perfectly fit the shape of the cable
- Long service life without deterioration of material properties



l <del>-</del>			L			
_			d			
				illillilli		
ble 1: Armor R	ods					
			Length.	Nbr of	Rod Dia.	
P/N*	Min. (mm)	Max. (mm)				Weight
P/N*		Max. (mm)	(mm)	Rod	(mm)	(Kg)
P/N* 113750X085	Min. (mm) 8.54	Max. (mm) 10.01				
		1 1	(mm)	Rod	(mm)	(Kg)
113750 <b>X</b> 085	8.54	10.01	(mm) 1000	Rod 10	(mm) 3.07	(Kg) 0.214
113750 <b>X</b> 085 113750 <b>X</b> 100	8.54 10.02	10.01 11.51	(mm) 1000 1000	10 11	(mm) 3.07 3.07	(Kg) 0.214 0.240
113750 <b>X</b> 085 113750 <b>X</b> 100 113750 <b>X</b> 115	8.54 10.02 11.52	10.01 11.51 13.26	(mm) 1000 1000 1000	10 11 13	(mm) 3.07 3.07 3.07	(Kg) 0.214 0.240 0.280
113750X085 113750X100 113750X115 113750X132	8.54 10.02 11.52 13.27	10.01 11.51 13.26 15.50	(mm) 1000 1000 1000 1000	10 11 13 13	3.07 3.07 3.07 3.07 3.45	(Kg) 0.214 0.240 0.280 0.354
113750X085 113750X100 113750X115 113750X132 113750X155	8.54 10.02 11.52 13.27 15.51	10.01 11.51 13.26 15.50 17.80	(mm) 1000 1000 1000 1000	10 11 13 13 15	(mm) 3.07 3.07 3.07 3.45 3.45	0.214 0.240 0.280 0.354 0.409
113750X085 113750X100 113750X115 113750X132 113750X155 113750X178	8.54 10.02 11.52 13.27 15.51 17.81	10.01 11.51 13.26 15.50 17.80 18.50	(mm) 1000 1000 1000 1000 1000 1000	10 11 13 13 15	(mm) 3.07 3.07 3.07 3.45 3.45 3.45	0.214 0.240 0.280 0.354 0.409 0.437

