



Double steady-burning light NAVILITE-F-120-240V should be installed when used as a top light in areas or locations where the failure of a single unit could cause an obstruction to be totally unlighted



- 2 NAVILITE-F-48V (113965) and a bracket for the 2 lights P/N 113929
- Surge protection included
- $\frac{3}{4}$ "NPT threaded holes for mounting the system
- No losing part during installation

Electrical Characteristics	
Wattage	12 W
Life time	~10years
Main voltage	48VDC (-10%; +15%)

Mechanical Characteristics	
IP degree	IP65 in vertical position
Wiring	On 4 stripped wires (2 for each lamp)
Operating temperature	-40/+55°C
Weight	3kg
Wire cross section	from 1 to 2,5 mm ²
Attachment	vertical NPT threaded holes

Photometric Characteristics	
Luminous intensity	> 32,5 Cd
Color night time	Red fixed
Vertical beam spread	>10°
Horizontal beam spread	360°

Standards	
Standards compliance	ICAO annexe 14 chapter 6 (8th edition 07/2018), EASA (4th edition 2017)
Certification	FAA (AC 150/5345-43H) ETL verified

OBSTA • 29 boulevard Edgar Quinet • 75014 Paris • France • Tel: +33 1 41 23 50 10 • info AT obsta.com • obsta.com 20260209 - Document sujet à modification sans préavis

1 / 1