


NAVILITE-F-120-240V-DUAL [P/N: 113969-D]


Double steady-burning light NAVILITE-F-120-240V should be installed when used as a top light in areas or locations where the failure of a single unit could cause an obstruction to be totally unlighted



- 2 NAVILITE-F-120-240V P/N113969 and a bracket for the 2 lights P/N113928
- Surge protection included
- alarm normally close and normally open available on each light
- Vertical ¾"NPT threaded holes for mounting the system
- No losing part during installation







Electrical Characteristics	
Wattage	12 W
Life time	~10years
Main voltage	110VAC to 240VAC +/-10% 50/60Hz
Mechanical Characteristics	
IP degree	IP65 in vertical position
Wiring	On 4 stripped wires (2 for each lamp)
Operating temperature	-40/+55°C
Weight	3,1kg
Wire cross section	from 1 to 2,5 mm²
Attachment	vertical NPT threaded holes
Photometric Characteristics	
Luminous intensity	> 32,5 Cd
Color night time	Red fixed
Vertical beam spread	>10°
Horizontal beam spread	360°
Standards	
Standards compliance	ICAO annexe 14 chapter 6 (8th edition 07/2018), EASA (4th edition 2017)
Certification	FAA (AC 150/5345-43H) ETL verified